

901033-1013

PATENT

**METHOD OF AND APPARATUS FOR OFFSHORE MOORING****TECHNICAL FIELD**

This invention relates generally to the mooring of mobile offshore drilling units, floating production platforms, SPARs, and other vessels at offshore venues, and more particularly to a method of and apparatus for mooring at offshore venues which does not require the use of winches, fair leads, stoppers, or other appurtenances on the vessel being moored and which obviates the need for dynamic positioning systems in the offshore mooring of vessels.

5

10

TECHNICAL FIELD

**BACKGROUND AND SUMMARY OF THE INVENTION**

Mobile offshore drilling units (MODUs), floating production platforms (FPPs), SPARs, and similar vessels are often moored at offshore venues utilizing either preset catenary mooring lines or preset taut-leg mooring lines. Mooring is accomplished by first attaching a plurality of preset mooring lines to the vessel to be moored, and thereafter applying a predetermined tension to each of the mooring lines. Heretofore the necessary tension has been applied to the mooring lines utilizing winches mounted on the vessel to be moored.

Winches having sufficient capacity to be used in tensioning mooring lines of the type used in offshore mooring operations are exceedingly expensive, but are used only intermittently, such as during the initial mooring of the vessel upon which they are installed, during relocation of the vessel, and in response to changing conditions at the mooring site. Thus, a need exists for method of and apparatus for mooring MODUs, FPPs, SPARs, and similar vessels at offshore venues which does not require the installation of mooring winches on the vessel to be moored.

Offshore mooring can also be accomplished using a technique known as dynamic positioning. The dynamic positioning technique involves the use of one or more propulsion devices mounted on the vessel to be moored which

are operated to maintain the vessel at a specified location as determined by GPS technology. Although generally satisfactory in operation, dynamic positioning systems require the consumption of substantial amounts of fuel and are therefore expensive to operate. The fuel consumption necessary in the operation of dynamic positioning systems also raises environmental concerns.

The present invention comprises a method of and apparatus for offshore mooring which fulfills the foregoing and other requirements long since found lacking in the prior art. In accordance with a first embodiment of the apparatus of the invention, a clamping apparatus is provided at the distal end of either a preset catenary mooring line or a preset taut-leg mooring line. A wire or chain pendant extends from the vessel to be moored through the clamping apparatus. The distal end of the pendant is connected to a line which extends to a winch mounted on an anchor handling vessel. The winch is utilized to pull the pendant through the clamping apparatus until a predetermined tension is exerted on the mooring line and the pendant. The clamping apparatus is then actuated to securely clamp the pendant to the mooring line while maintaining the predetermined tension. In this matter the tension necessary to properly moor the vessel at the

offshore site is achieved without requiring the use of mooring winches on the vessel being moored.

In accordance with more specific aspects of the invention, a remotely operated vehicle (ROV) is deployed from the anchor handling vessel. A chain is mounted at the distal end of the pendant, and a submersible buoy is mounted at the distal end of the chain. The line deployed from the winch on the anchor handling vessel is secured to the pendant during tensioning operations.

The chain portion of the pendant extends around a pulley or sheave mounted on the clamping apparatus. When the predetermined tension has been applied to the mooring line and the pendant by the winch on the anchor handling vessel, the ROV actuates the clamping apparatus to securely clamp the pendant to the mooring line while maintaining the predetermined tension. Thereafter, the ROV disengages the vessel from the pendant.

In accordance with a first embodiment of the method of the invention, a clamping apparatus is mounted at the distal end of a preset mooring line. The clamping apparatus is brought on board an anchor handling vessel. A pendant extending from a vessel to be moored is directed through the clamping apparatus and is secured to a line extending from a winch mounted on the anchor handling vessel. The clamping apparatus having the pendant

extending therethrough is then lowered into the sea, and the winch on the anchor handling vessel is operated to apply increasing tension to the pendant and the mooring line until a predetermined tension is achieved. An ROV  
5 deployed from the anchor handling vessel is then utilized to actuate the clamping apparatus to securely clamp the pendant into engagement with the mooring line while maintaining the predetermined tension, and thereafter to disengage the pendant from the anchor handling vessel.

10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
2212  
2213  
2214  
2215  
2216  
2217  
2218  
2219  
2220  
2221  
2222  
22

**BRIEF DESCRIPTION OF THE DRAWINGS**

A more completely understanding of the invention may be had by reference to the following Detailed Description when taken in conjunction with the accompanying Drawings, wherein:

FIGURE 1 is a diagrammatic illustration of an apparatus for offshore mooring comprising a first embodiment of the invention;

FIGURE 2 is an illustration similar to FIGURE 1 showing the apparatus thereof at the completion of a mooring installation;

FIGURE 3 is an enlargement of a portion of FIGURE 1;

FIGURE 4 is a sectional view taken along the line 44 in FIGURE 3 in the direction of the arrows;

FIGURE 5 is a transverse sectional view taken through the apparatus of FIGURE 3 and further illustrating the clamping mechanism thereof;

FIGURE 6 is an illustration similar to FIGURE 3 illustrating a clamping mechanism comprising a stopper arm;

FIGURE 6A is a view similar to FIGURE 6 illustrating a variation of the mechanism shown therein;

FIGURE 7 is a diagrammatic illustration of a early steps in the method comprising the first embodiment of the invention;

FIGURE 8 is a diagrammatic illustration of a later step in the method of FIGURE 7;

FIGURE 9 is a diagrammatic illustration of a later step in the method of FIGURES 7 and 8;

5        FIGURE 10 is a diagrammatic illustration of a later step in the method of FIGURES 7, 8, and 9;

FIGURE 11 is a diagrammatic illustration of a later step of the method illustrated in FIGURE 7, 8, 9, and 10;

10        FIGURE 12 is an illustration of a later step in the method of the invention illustrated in FIGURES 7, 8, 9, 10, and 11;

FIGURE 13 is an illustration of a later step in the method illustrated in FIGURES 7, 8, 9, 10, 11, and 12;

15        FIGURE 14 is a diagrammatic illustration of a later step in the method illustrated in FIGURES 7, 8, 9, 10, 11, 12, and 13;

FIGURE 15 is a diagrammatic illustration of the concluding steps of the method illustrated in FIGURES 7 through 14, inclusive;

20        FIGURE 16 is a diagrammatic illustration of a method of and apparatus for offshore mooring comprising a second embodiment of the invention;

FIGURE 17 is a side view illustrating an apparatus for offshore mooring comprising a third embodiment of the invention;

25

FIGURE 18 is a perspective view further illustrating the apparatus of FIGURE 17;

FIGURE 19 is a perspective view similar to FIGURE 18 in which certain parts have been broken away more clearly to illustrate certain features of the invention;

FIGURE 20 is a perspective view further illustrating the apparatus of FIGURE 17;

FIGURE 21 is a diagrammatic illustration of early steps in a method of offshore mooring comprising a fourth embodiment of the invention;

FIGURE 22 is a diagrammatic illustration of a later step in the method of FIGURE 21;

FIGURE 23 is a diagrammatic illustration of a later step in the method of FIGURES 21 and 22;

FIGURE 24 is a diagrammatic illustration of a later step in the method of FIGURES 21 through 23, inclusive;

FIGURE 25 is a diagrammatic illustration of a later step in the method of FIGURES 21 through 24, inclusive;

FIGURE 26 is a diagrammatic illustration of a later step in the method of FIGURES 21 through 25, inclusive;

FIGURE 27 is a diagrammatic illustration of a later step in the method of FIGURES 21 through 26, inclusive;

FIGURE 28 is a diagrammatic illustration of a later step in the method of FIGURES 21 through 27, inclusive;



FIGURE 29 is a diagrammatic illustration of a later step in the method of FIGURES 21 through 28, inclusive;

FIGURE 30 is a diagrammatic illustration of a later step in the method of FIGURES 21 through 29, inclusive;

5        FIGURE 31 is a diagrammatic illustration of a mooring installation constructed in accordance with the method of FIGURES 21 through 30, inclusive;

10        FIGURE 32 is a diagrammatic illustration of a method of offshore mooring comprising a fifth embodiment of the invention; and

FIGURE 33 is a diagrammatic illustration of a method of offshore mooring comprising a sixth embodiment of the invention.

**DETAILED DESCRIPTION**

Referring now the Drawings, and particularly to Figures 1 through 6 thereof, there is shown method of and apparatus for offshore mooring 20 comprising a first embodiment of the invention. In accordance with the invention, a vessel to be moored (VTBM) 22 is located at an offshore venue. The VTBM may comprise a mobile offshore drilling unit, a floating production platform (monohull or semisubmersible), a SPAR, or any other vessel requiring offshore mooring. A plurality of wire or chain mooring attachment pendants 24 are secured to the VTBM at spaced apart locations around the circumference thereof. Each mooring attachment pendant 24 is secured to the VTBM through a padeye 26. Each padeye 26 is provided with a tension measuring device such as a strain gauge. The function of the tension measuring device is to produce an output indicative of the tension applied to its associated padeye 26 by the mooring attachment pendant 24 secured thereto.

The apparatus for offshore mooring 20 further includes a plurality of mooring lines 30. As will be appreciated by those skilled in the art, each mooring line 30 comprises multiple components, including wire, chain, connectors, etc. The major part of each mooring line 30 is installed before the VTBM is on site; therefore, the mooring lines

30 are referred to as preset mooring lines. Each preset mooring line 30 extends from an anchor 32 which is securely engaged with the sea floor 34. The preset mooring lines 30 may be secured to the sea floor by drag embedment anchors, vertically loaded anchors, driven piles, suction anchors, suction embedded plate anchors, or other anchor types suitable for offshore mooring.

As will be appreciated by those skilled in the art, the preset mooring lines 30 may comprise either catenary preset mooring lines or taut-leg preset mooring lines. The mooring lines 30 are equal in number to the number of mooring attachment pendants 24 secured to the VTBM, and are positioned around the site at which the VTBM is to be moored in a more or less circular array.

In accordance with the first embodiment of the invention, each preset mooring line 30 has a clamping apparatus 40 secured to the distal end thereof. Referring particularly to Figures 3 and 4, each clamping apparatus 40 comprises a box shaped frame 41 having a padeye 42 mounted at one end thereof. The padeye 42 is utilized to secure the clamping apparatus 40 to its associated preset mooring line 30.

The clamping apparatus 40 includes a slotted sheave or pulley 43 which is rotatably supported on the frame 40 by suitable bearings 44. The sheave 43 includes a wide

outer slot and a narrow inner slot. The clamping apparatus 40 further includes a clamping mechanism 46 mounted at the opposite end of the frame 42 from the padeye 42.

As is best shown in Figure 3, the clamping mechanism 46 may comprise a chain stopper 47 which is slidably supported in the frame 41 of the clamping apparatus 40 for movement in the direction of the arrows 48. A threaded member 49 is threadably engaged with the frame 42. Therefore, upon rotation of the threaded member 49, the chain stopper 47 is selectively positioned relative to the frame 41. The threaded member 49 extends to a socket 50 which adapted for actuation by a remote operated vehicle (ROV).

Referring to Figure 6, there is shown an alternative clamping mechanism 52 which may be incorporated in the clamping apparatus 40 in lieu of the clamping mechanism 46 shown in Figures 3 and 5. The clamping mechanism 52 comprises a stopper arm 54 which is pivotally supported on the frame 41 of the clamping apparatus 40 by a cylindrical member 56. The stopper arm 54 is spring biased to pivot in the direction indicated by the arrow 58. An arm 60 is secured to the stopper arm 54 and extends out of the frame 41 of the clamping apparatus 40 for actuation by a remote operated vehicle to selectively pivot the stopper arm 54 in the direction opposite of the arrow 58.

As is shown in Figure 6, the stopper arm normally prevents a chain extending through the clamping apparatus 40 and around the slotted sheave 43 thereof for moving rightwardly (Figure 6). However, the chain is free to move in the leftward direction (Figure 6) because the stopper arm 54 simply pivots upwardly against the action of its spring bias until sufficient leftward movement has occurred for the stopper arm 54 to engage the next link of the chain. Whenever the remote operated vehicle is utilized to actuate the arm 60 to pivot the stopper arm 54 in the direction opposite that of the arrow 58, the chain is allowed to move freely in the rightward direction (Figure 6).

Referring to Figure 6A, there is shown a clamping apparatus 40' which may be used in lieu of the clamping apparatus 40 of Figure 6. Many of the component parts of the clamping apparatus 40' are substantially identical to component parts comprising the clamping apparatus 40 as illustrated in Figure 6 and described hereandabove in conjunction therewith. Such identical component parts are designated in Figure 6A which are the same reference numerals utilized in Figure 6 but are differentiated therefrom by means of a prime (') designation.

The clamping apparatus 40A differs from the clamping apparatus 40 in that it is provided with a guide roller 61

which guides the chain through the clamping mechanism 52' and into the slotted pulley 43'. This assures that the chain will be properly oriented relative to the component parts of the clamping mechanism 52' regardless of the angular orientation of the chain relative to the angular orientation of the mooring line.

Referring again to Figure 1, each mooring attachment pendant 24 may have one or more adjustment pendants 64 secured thereto depending upon the length of the associated preset mooring line 30 and the depth of the ocean at the venue comprising the location of the VTBM 22. A chain 66 is secured to the distal end of the mooring attachment pendant 24 and any adjustment pendants connected thereto. The mooring attachment pendant 24, any adjustment pendants 64 connected thereto, and the chain 66 comprise a pendant 67 which is broadly defined to include all of the components connected between the padeye 26 of the VTBM 22 and the clamping apparatus 40.

The chain 66 extends through the clamping mechanism of the clamping apparatus 40 and around the pulley 43 thereof. A submersible buoy 68 is secured to the distal end of the chain 66.

The apparatus for offshore mooring 20 further including a large anchor handling vessel 80. The vessel 80 is provided with a winch 82. A line 84 extends from the

winch 82 and is secured to the pendant 67. As is indicated by the arrows 86, the winch 82 of the vessel 80 is utilized to apply an upwardly directed force of the distal end of the chain 66 thereby applying increasing tension to the pendant 67 and to the preset mooring line 30.

The vessel 80 also deploys an ROV 90. After the winch 82 of the vessel 80 has applied the predetermined tension to the pendant 67 and to the preset mooring line 30, the ROV 90 actuates the clamping mechanism of the clamping apparatus 40 to move the either chain stopper 47, or the stopper arm 54, or the stopper arm 54' into engagement with the chain 66. In this manner the pendant 67 is securely clamped to the preset mooring line while maintaining the predetermined tension throughout the entire connection between the VTBM 22 and the anchor 32. After the clamping mechanism has been actuated to securely clamp the pendant 47 into engagement with the mooring line 30, the ROV 90 disengages the line 84 from the submersible buoy 68.

The configuration of each of the mooring lines 30, the clamping apparatus 40 connected thereto, and the associated pendant 67 at the conclusion of mooring operations is illustrated in Figure 2. The distal end of the chain 66 is maintained in a vertical orientation by the submersible buoy 68. This allows re-engagement of the pendant 67 by a line extending from an anchor handling vessel in the

event that an adjustment in the tension that is applied to the VTBM by one or more of the mooring lines attached thereto is required.

As will be appreciated by those skilled in the art, proper mooring of the VTBM 22 typically requires a plurality of pendants and associated preset mooring lines. Mooring of the VTBM 22 is accomplished by actuating the chain 66 comprising each of the pendants to apply the required tension thereto. After tension has been applied to all of the pendants extending from a particular VTBM, further adjustments in the tensioning of particular pendants may be required. After all of the pendants and the associated preset mooring lines connected to the VTBM have been properly tensioned, the vessel 80 departs and the VTBM 22 remains securely moored.

A more complete understanding of the method of offshore mooring 20 comprising the present invention may be had by reference to Figures 7 through 15, inclusive. A plurality of preset mooring lines 30 are installed at spaced apart locations around a mooring venue. Each preset mooring line 30 includes an anchor 32 which is securely engaged with the sea floor 34, and extends from the anchor 32 along the surface of the sea floor 34 to a clamping apparatus 40. A recovery pendant 92 is initially secured



to the clamping apparatus 40 and is maintained in a vertical orientation by a submersible buoy 94.

A vessel 80 is maneuvered above the location of the clamping apparatus 40. A line 96 is extended downwardly from the vessel 80 as indicated by the arrows 98. An ROV 90 is deployed from the vehicle 80 and is utilized to secure the line 96 into engagement with the recovery pendant 92.

Referring to Figures 8 and 9, the line 96 is utilized to bring the clamping apparatus 40 on board the vessel 80. A line 102 is secured to the clamping apparatus 40. The line 102 is paid out in the manner indicated by the arrows 104 as the vessel 80 moves toward a VTBM 22 as indicated by the arrow 106.

As is shown in Figure 10, the vessel 80 continues to move toward the VTBM 22 in the direction indicated by the arrow 106. Meanwhile, the line 102 continues to pay out. A crane 108 mounted on the VTBM 22 passes a mooring attachment pendant 24 associated with the mooring line 30 to the vessel 80.

Referring to Figure 11, the vessel 80 next moves away from the VTBM 22 as indicated by the arrow 110. Adjustment pendants 64 are connected to the mooring pendant 24 as needed and are paid out as indicated by the arrow 112. The line 102 is drawn on board the vessel 80 as indicated by

the arrows 114, thereby moving the clamping apparatus 40 upwardly.

As is shown in Figure 12, a chain 66 is connected to the distal end of the pendant 24, it being understood that one or more adjustment pendants 64 may be connected between the chain 66 and the pendant 24. The chain 66 is paid out from the vessel 80 as indicated by the arrow 116.

Referring to Figures 13 and 14, the clamping apparatus 40 is brought on board the vessel 80. A line 118 is extended through the clamping apparatus 40 while the clamping apparatus 40 is on board the vessel 80. The distal end of a line 118 is in turn connected to a line 122 extending from a winch on board the vessel 80. A line 124 is connected to the clamping apparatus 40 and is utilized to lower the clamping apparatus as indicated by the arrows 126.

Lowering of the clamping apparatus 40 continues until the chain 66 passes through the clamping apparatus 40. At this point the lines 122 and 124 are recovered onto the vessel 80 until the clamping apparatus 40 and the chain 66 extending therethrough are either adjacent to or on board the vessel 80. A submersible buoy 68 is then inserted at the distal end of the chain 66. The lines 122 and 124 are then paid out until the clamping apparatus 40 and the chain 66 are positioned as shown in Figure 11.

The ROV 80 is then employed to disengage the line 124 from the clamping apparatus 40. The line 124 is recovered on board the vessel 80 as indicated by the arrow 130. The winch 82 on board the vessel 80 applies an upwardly directed force to the chain 66 as indicated by the arrow 132. When the predetermined tension has been applied to the pendant and the preset mooring line, the ROV 80 is utilized to actuate the clamping apparatus 40 to securely clamp the pendant to the preset mooring line while maintaining the predetermined tension thereon. The ROV 80 is thereafter utilized to disengage the line 122 from the chain 66.

Referring to Figure 16, there is shown a method of and apparatus for offshore mooring 150 comprising a second embodiment of the invention. In accordance with the second embodiment of the invention, a pendant 152 extends from a vessel to be moored (VTBM) 153 and is secured to a clamping apparatus 154. The pendant 152 is substantially identical to the pendant 67 illustrated in Figures 1 through 15, inclusive, and described hereandabove in conjunction therewith, except that the pendant 152 does not necessarily have a chain secured at its distal end. The clamping apparatus 154 is substantially identical in construction and function to the clamping apparatus 40 as illustrated in Figures 3 through 6, inclusive, and includes a clamping

mechanism such as the clamping mechanism 46 shown in Figures 3 and 5, or the clamping mechanism 52 shown in Figure 6, or the clamping mechanism 52' of Figure 6A.

5 A mooring line 156 extends from a suitable anchor (not shown in Figure 16). The mooring line 156 is substantially identical in construction and function to the mooring line 30 as illustrated in Figures 1 through 15, inclusive, except that the mooring line 156 has a chain 158 secured to the distal end thereof. A submersible buoy 160 is  
10 secured to the distal end of the chain 158.

As will be appreciated by those skilled in the art, the deployment and function of the method of and apparatus for offshore mooring 150 comprising the second embodiment of the invention are substantially identical to the  
15 deployment and operation of the method of and apparatus for offshore mooring 20 comprising the first embodiment of the invention. The first and second embodiments of the invention differ primarily in the fact that the clamping apparatus 154 of the second embodiment of the invention is  
20 secured to the pendant 152 as opposed to being secured to the mooring line. This in turn causes the tensioning force to be applied by an anchor handling vessel to a chain secured at the distal end of the mooring line and extending through the clamping mechanism and around the slotted  
25 sheave of the clamping apparatus 154.

Referring to Figures 17 through 20, inclusive, there is shown an apparatus for offshore mooring 190 comprising a third embodiment of the invention. The apparatus 190 comprises a pin 192. The remaining components of the apparatus 190 are rotatably and/or pivotally supported on the pin 192. The apparatus 190 further includes a slotted pulley or sheave 194 which is rotatably supported on the pivot pin 192. The slotted pulley 194 includes an inner narrow slot 196 which receives the nominally vertically oriented links of a chain 198, and an outer wide slot 200 which receives the nominally horizontally oriented links of the chain 198.

The apparatus for offshore mooring 190 further includes an attachment arm 202 which is pivotally supported on the pin 192. A shackle 204 is mounted at one end of the attachment arm 202, and a shackle 206 is mounted at the opposite end thereof. The shackle 204 is utilized whenever it is necessary to raise or lower the apparatus for offshore mooring 190 relative to an anchor handling vessel. In such instances a line extending from the anchor handling vessel is secured to the shackle 204 of the apparatus 190 by a remote operated vehicle.

The shackle 206 has a chain 208 connected thereto. When the apparatus for offshore mooring 190 is utilized in conjunction with the method for offshore mooring

illustrated in Figures 1 through 15, inclusive, and described hereinabove in conjunction therewith, the chain 208 comprises the distal end of the mooring line 30 and the chain 198 comprises the distal end of the pendant 67. In the case of the method of offshore mooring illustrated in Figure 14 and described hereinabove in conjunction therewith the chain 208 comprises the distal end of the pendant 152 and the chain 198 comprises the distal end of the mooring line 156.

The apparatus for offshore mooring 190 further comprises a clamping apparatus 210 which is pivotally supported on the pin 192. Referring particularly to Figure 19, the clamping apparatus 210 includes a rectangular chain guiding aperture 212 which receives the chain 198 therethrough. The aperture 212 extends to a guide plate 214 having a slot 216 formed therein which receives the nominally vertically oriented links of the chain 198.

The clamping apparatus 210 further includes a clamping mechanism 220. Referring momentarily to Figure 17; the clamping mechanism 220 includes a stopper arm 222 which is pivotally supported for movement between the full line position and the dashed line position as shown in Figure 17. Referring to Figure 19, the stopper arm 222 has a curved chain engaging plate 224 mounted at the distal end thereof which normally engages one of the nominally

vertically oriented links of the chain 198 to prevent movement of the chain 198 in the direction of the arrow 226 (Figure 19).

Referring to Figures 18 and 19, the clamping apparatus 210 comprises spaced parallel plates 230 extending on opposite sides of the slotted pulley 194. The plates 230 are interconnected by a reinforcing member 232 and by reinforcing members 234 which are mounted on the underside of the guide plate 214. An aperture 236 extends through one of the guide plates 230, it being understood that both guide plates 230 may be provided with apertures 236, if desired. The aperture 236 provides access to the stopper arm 222 by a tool mounted on a remote operated vehicle, thereby permitting the remote operated vehicle to selectively pivot stopper arm 222 from the position shown in full lines in Figure 17 to the position shown in dashed lines therein. In this manner the stopper arm 222 is disengaged from the chain 198 thereby allowing the chain 198 to move in the direction of the arrow 226 (Figure 19). As will be appreciated by those skilled in the art, the stopper arm 222 is normally retained in the position of the full lines in Figure 17 by a suitable spring.

A method of offshore mooring 250 comprises a fourth embodiment of the invention as illustrated in Figures 21 through 31, inclusive. Referring first to Figure 21, a

vessel to be moored (VTBM) 252 is located at an offshore mooring site. Although the VTBM illustrated in Figures 21 through 31 is a mobile offshore drilling unit, the method of offshore mooring 250 is equally adapted to the mooring of floating production platforms, SPARs, as well as other vessels requiring offshore mooring. The VTBM 252 has a plurality of connection pendants 254 secured thereto.

A mooring line 260 includes a ground chain 262 which is secured to an anchor 264. The anchor 264 is securely engaged with the sea floor 266 and may comprise a drag embedment anchor, a vertically loaded anchor, a driven pile, a suction anchor, a suction embedded plate anchor, or any other anchor type adapted for mooring in deep waters. A submersible buoy 268 is connected to the distal end of the mooring line 260.

Referring to Figure 22, an anchor handling vessel 270 receives the connection pendant 254 from the VTBM 252 and connects an insert wire 272 thereto. The anchor handling vessel 270 pays out the insert wire 272 as indicated by the arrows 274 and moves away from the VTBM 252 as indicated by the arrow 276.

As is shown in Figure 23, a tensioning chain 280 is inserted between the insert wire 272 and a pendant 282. The pendant 282 is in turn connected to a work wire 284. The work wire 284 is paid out as indicated by the arrow 286



while the anchor handling vessel 270 moves further away from the VTBM 282 as indicated by the arrow 288.

Referring to Figure 24, the anchor handling vessel 270 pays out the work wire 284 until it arrives at the location of the buoy 268. The anchor handling vessel 270 recovers the buoy 268 and secures the distal end of the mooring line 260 in a sharks jaws retainer. The buoy 268 is stored on the anchor handling vessel 270.

As is shown in Figures 25 and 26, the distal end of the mooring line 260 is connected to a clamping apparatus 290 constructed in accordance with the present invention. The work wire 284 is extended through the clamping apparatus 290. A line 292 is secured to the clamping apparatus 280 and is utilized to lower the clamping apparatus 290 from the anchor handling vessel 270. A remote operated vehicle (ROV) 294 is deployed from the anchor handling vessel 270 and is utilized to inspect and observe the clamping apparatus 290, the connection of the mooring line 260 thereto and the movement of the work wire 284 through the clamping apparatus 290 as the clamping apparatus 290 moves downwardly.

Referring to Figures 27 and 28, the anchor handling vessel recovers the work wire 284 through the clamping apparatus 290. The ROV 294 continues to monitor the connection between the line 292 and the clamping apparatus

290 and the movement of the work wire 294 through the clamping apparatus 290. The foregoing procedure continues until the chain section 280 is received in the clamping apparatus 290. At this point the pendant 282 has passed  
5 through the clamping apparatus 290. The ROV actuates the clamping apparatus 290 to engage the chain suction 280.

As is best shown in Figure 29, the anchor handling vessel next reverses course so that it moves in the direction indicated by the arrow 296. The line 292 is paid  
10 out until it becomes slack. The engine power of the anchor handling vessel 270 is applied to the chain 280 whereby the chain 280 is drawn through the clamping apparatus 290 until a predetermined tension is applied to the VTBM and to the mooring line 260. The clamping apparatus 290 clamps the  
15 mooring line 260 to the line extending from the VTBM 252 comprising the pendant 254, the insert line 272, and the chain 280.

The next step of the method is illustrated in Figure 30. The ROV 294 disconnects the line 292 from the clamping apparatus 290, and the line 292 is recovered onboard the  
20 anchor handling vessel 270. The pendant 282 is deployed from the anchor handling vessel 270 and the upper end thereof is secured in a sharks jaws retainer. The submersible buoy 268 is secured to the upper end of the  
25 pendant 282 while the work wire 284 remains secured to the

pendant 282 below the buoy 268. The pendant 282 is released from the sharks jaws retainer and the work wire 284 is utilized to lower the clamping apparatus 290, the upper end of the chain 280, the pendant 282, and the buoy 268. When the lowering operation is complete, the work wire 284 is disconnected from the pendant 282 by the ROV 294, whereupon the component parts are positioned as illustrated in Figure 31.

A method of offshore mooring 190 comprising a fifth embodiment of the invention is illustrated in Figure 32. In accordance with the fifth embodiment of the invention, a vessel to be moored (VTBM) 302 is moored at a mooring site 304 which is coincident with the illustration of the VTBM in full lines.

The VTBM 302 is initially positioned as indicated in dashed lines wherein the VTBM is somewhat displaced from the mooring site 304. With the VTBM situated at its displaced location, conventional mooring lines 306 are connected between anchoring points 307 and the VTBM 302. As will be appreciated by those skilled in the art, because the VTBM is situated at a location somewhat offset from the mooring site 304, sufficient slack is provided in the conventional mooring 306 to facilitate installation thereof.

After the conventional mooring lines 306 have been installed, the VTBM 302 is moved to the installation site 304. Thereafter, apparatus for offshore mooring 308 comprising the present invention are connected to the VTBM.

5 The apparatus for offshore mooring 308 may comprise any of the embodiments disclosed herein and are adapted for activation by an anchor handling vessel. In this manner the anchor handling vessel is employed not only to apply predetermined tension to the apparatus for offshore mooring  
10 308, but also to the conventional mooring lines 196.

Referring to Figure 33, the method of and apparatus for offshore mooring 310 comprising a sixth embodiment of the invention is illustrated. In accordance with the fourth embodiment of the invention, a vessel to be moored  
15 (VTBM) 312 is situated at a mooring site 314 which is coincident with the outline of the VTBM as illustrated in Figure 33. Conventional mooring lines 316 are connected to the VTBM. The conventional mooring lines 316 provide the VTBM with a predetermined mooring rating, for example,  
20 a ten year hurricane rating.

In accordance with the sixth embodiment of the invention, supplemental mooring systems 320 constructed in accordance with the present invention in addition to the conventional mooring lines 316. Each of the supplemental  
25 mooring systems 320 comprises a mooring line, a clamping

apparatus, and a pendant extending from the VTBM to the mooring apparatus. Either the mooring line or the pendant extends through the clamping apparatus to the distal end adapted for the engagement by a line extending from an anchor handling vessel. The anchor handling vessel is utilized to apply a predetermined tension to each of the supplemental mooring systems 320. In this manner the mooring rating for the VTBM 312 is substantially raised, for example, from a ten year hurricane rating to a fifty year hurricane rating.

It will therefore be understood that the method of and apparatus for offshore mooring comprising the present invention is adapted for mooring mobile offshore drilling units, floating production platforms, SPARs, and other apparatus at offshore venues without requiring the use of mooring winches on the apparatus to be moored. Because the mooring winches which have heretofore been required to effect mooring operations at offshore venues are extremely expensive, the use of the method and apparatus of the present invention results in substantial cost savings.

Although preferred embodiments of the invention have been illustrated in the accompanying drawings and described in the foregoing Detailed Description, it will be understood that the invention is not limited to the embodiments disclosed, but is capable of numerous

rearrangements, modifications, and substitutions of parts and elements without departing from the spirit of the invention.

FOR THE UNITED STATES PATENT OFFICE